



DIRECTIONAL LIGHTS RXD-02-TS SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Copper tube shield bullet and cast brass adjustable swivel with 240° rotation

LENS: High impact clear tempered convex glass

O-RING: High temperature red silicone

LAMP SUPPLIED: 20w MR16 FL(BAB) 5000 hours average rating (50w max)

LAMP OPTIONS: We recommend 20w MR16 ULTRA10,000 hours average rating; 20w MR16 TITAN 18,000 hours average rating; 4w ARROW LED 50,000 average rating

SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires



WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

MOUNTING: FA-03 black 9" ABS stake threaded 1/2" NPS

FINISH: Copper - Unfinished only



RXD-02-TS-COP
shown on FA-24-BRS

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
RXD-02-TS-COP	Copper Tube Shield Bullet	20w MR16 FL(BAB)	3.0 lbs.

LAMP AND STAKE **INSTALLED** TO SAVE YOU TIME AND MONEY



MOUNTING ACCESSORIES

FA-01/BRS 15" 381mm, 1.63" 41mm, 2.65" 67mm

FA-03/BRS 9.00" 229mm, 2" 51mm

FA-03-RX/-BRS 7.00" 178mm, 2" 51mm

FA-03-LG 9.00" 229mm, 3" 76mm

FA-22-CST/-BRS 5.75" 146mm, 3.5" 89mm, 1.125" 29mm

FA-22-TREE (10"-41")

FA-24-MD-CST-PC/-BRS 2.65" 67mm, 1.4" 36mm

FA-24-MD-CST/-BRS 2.65" 67mm, 1.4" 36mm

FA-24-BRS 0.9" 23mm, 3" 76mm

FA-24-TREE 2.2" 51mm

FA-111 4.75" 121mm, 0.875" 22mm

FA-24-LG-CST / -BRS 0.875" 22mm

FA-24-LG-DH-SPUN/-BRS 0.875" 22mm

FA-24-LG-DH-CST/-BRS 0.875" 22mm

FA-30-4 4" 102mm, 8" 203mm

FA-30-8 8" 203mm

FA-30 10" 254mm

FA-31 13" 330mm

FA-32 16" 406mm

FA-33 21" 533mm

FA-34 21" 533mm

STEM EXTENSIONS

BEAM/GLARE CONTROL ACCESSORIES

- FA-08-21** Round 1/4" Hex Cell Louver
- FA-11-33-BLUE** Blue Tempered Glass Lens
- FA-11-33-GREEN** Green Tempered Glass Lens
- FA-11-33-AMBER** Amber Tempered Glass Lens
- FA-11-33-RED** Red Tempered Glass Lens
- FA-98-33** Linear Spread Tempered Glass Lens
- FA-104-17** Wide Spread Sandblasted Glass Lens Softener

**MR11 & MR8 MODELS
AVAILABLE IN COPPER**

SEE RXD-03-TS & -04-TS
CUT SHEET

JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC.®
25301 COMMERCENTRE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390