



WALL MOUNT LIGHTS SL-13 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Formed solid brass lantern on wall mount with brass canopy and extruded brass arm

LENS: Gold iridescent glass; optional plastic White Cracked Ice available (-ICE)

LAMP SUPPLIED: 18w S8 #1141; 1200 hours average rating (25w max)

LAMP OPTIONS: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or 3w 50,000 hours average rating OMNI-3 LED (-LED3)

SOCKET: Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s)

WIRING: Black 5 foot 18/2 zip cord from base of fixture (12v only)
For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

MOUNTING: Back plate hardware and screws supplied

FINISH: Unfinished brass. Optional finishes available




SL-13-BRS


ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
SL-13-BLT	Black Powder Coat Brass Wall Mount Lantern	18w S8 #1141	2.0 lbs.
SL-13-BRS	Brass Wall Mount Lantern	18w S8 #1141	2.0 lbs.

LIGHT DISTRIBUTIONS AND PHOTOMETRICS



SL-13
Half Spread Photometrics
4 ft. (1.2m) radius



JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630
 www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT